



TECHNICAL DATA

O.RING	EPDM
SLIPPER	PTFE+CARBON FIBRE
FILTER	700 MICRON
NOZZLES POSITIONS	2-4
NOZZLES TYPE	1/8"NPT
MAX OPERATING FLOW	60 L/min
MAX OPERATING PRESSURE	150 bar
MAX OPERATING TEMPERATURE	90 °C
MATERIAL	INOX AISI 316
CONICAL GEARS	FIXED Z=29 ROTATING Z=31
MODULE	1
COMPLETE CYCLE	31 ROTATIONS
COMPLETE CYCLE TIME	30 SEC
ROTATION SPEED	60 RPM
WEIGHT	7.5 KG

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
	FOGLIO	XXXX				
GREZZO ~ = ✓	DATA	XX.XX.XX				
	TOLLERANZE GENERALI classe m UNI-EN 22768/1					
SGROSS. ▽ = 3.2/	0÷6	6÷30	30÷120	120÷400	400÷1000	1000÷2000
	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2
FINITURA ▽▽ = 1.6/	NOTE: file: XC 061 AAH cm					
	DESCRIZIONE: APPLICATION DRAWING XC031_180°FR-AAM.01					
RETTIFICA ▽▽▽ = 0.8/	DISEGN.: GR					CONTR.: DM
	DATA: 07.05.08					MOD.
SCALA		1:2	A4	0		
CODICE: XC031_180°FR-AAM.01						

Bolondi
CLEANING HEADS
MONTECCHIO E. (RE) - ITALY